

Amendments to the Claims:

The present listing of the claims replaces all past listings of the claims:

Listing of claims:

Claim 1. (Currently Amended) Rotary press ~~comprising with a plurality of anti-rotation secured shafts and exchangeable punches arrayed in a circle for rotating about the rotary press, attached thereto,~~ Comprising
each of said punches being an exchangeable punch disposed rotatably about a punch shaft, the punch shaft being secured against rotation with respect to its longitudinal axis,
a connecting component residing in a circumferential recess of a stem of the punch effecting a rotational connection of the punch with the punch shaft,
an external component residing substantially externally of the circle, a second zone of the external component residing adjacent the circle,
a shell surface of the punch comprising a first zone which engages is engageable with the a second zone of an the external component, wherein the second zone is being fixed at a location opposite a punch circumference with respect to the rotation of the punches about the circle, the first zone and second zone together comprising a means for effecting, and the external component interacts with the shell surface of the punch by a force-locking or a positive locking effect in such a way that the punch receives a turning movement at a defined point of the a pitch circle of the punch circumference.

Claim 2. (previously Amended) Rotary press according to Claim 1, wherein the shell surface of the punch comprises the first zone for interacting with the second zone of the external component.

Claim 3. (Currently Amended) Rotary press according to Claim 1, wherein the external component is separately adjustable and moveable into ~~different~~ different defined points of the ~~pitch circle, and wherein the external component is being~~ radially positionable around the ~~pitch circle of the punch circumference.~~

Claim 4. (previously Amended) Rotary press according to Claim 1, wherein the external component has a bearing location which is radially elastic.

Claim 5. (previously Amended) Rotary press according to Claim 1, wherein a seal seals a joint between the punch shaft and the punch.

Claim 6. (previously Amended) Rotary press according to Claim 1, wherein the first zone of the shell surface of the punch interacts with the second zone of the external component is a separated and exchangeable element of the punch.

Claim 7. (previously Amended) Rotary press according to Claims 1, wherein the first and second zones of the shell surface and the external component, respectively, comprise serration or friction surfaces.

Claim 8. (previously Amended) Rotary press according to Claim 7, wherein the serration or friction surfaces are low in mass and elastic in a circumferential direction.

Claim 9. (previously Amended) Rotary press according to Claim 8, wherein the second zone of the external component is an elastically yielding spring element disposed in a movement direction of the punch, such that the elastically yielding spring element can simultaneously absorb an occurring impact energy and, ensure a secure and reliable engagement into the first

zone of the shell surface of the punch.

Claim 10. (previously Amended) Rotary press according to Claim 8, wherein the first zone of the shell surface of the punch comprises a tooth profile adapted to the second zone of the external component.

Claim 11. (previously Amended) Rotary press according to Claim 8, wherein the second zone of the external component comprises at least two spring elements situated one behind the other in movement direction of the punch and arranged in a comb-like manner.

Claim 12. (Currently Amended) Rotary press comprising a plurality of dies and a plurality of punches arrayed in a circle for rotating about the rotary press, each of said punches being with anti-rotation secured shafts, an exchangeable punches attached to a punch shaft, the punch shaft being secured against rotation with respect to its longitudinal axis, and dies attached thereto, an external component residing substantially externally of the circle, a second zone of the external component residing adjacent the circle,
wherein
the dies ~~are~~being trunnion-supported and comprise on their outer sides a first zone which is engageable with a serration or a friction surface, which interacts with the second zone of an the external component, the second zone which is being fixed at a location on with respect to the -rotation of the punches about the rotary press circle opposite a punch circumference, the first zone and the second zone together comprising a means for effecting in a force-locking or positive locking manner, in such a way that the punchdies receives a rotational movement at a defined point of a pitch circle of a punch circumference.

Claim 13. (unchanged) Rotary press according to Claim 1, wherein the connecting component is a spring thrust piece.

Claim 14. (unchanged) Rotary press according to Claim 5, wherein the seal is a labyrinth seal.

Claim 15. (unchanged) Rotary press according to Claim 10, wherein the tooth profile is a trapezoidal or a saw tooth profile.